

https://journals.researchparks.org/index.php/IJOT e-ISSN: 2615-8140 | p-ISSN: 2615-7071 Volume: 4 Issue: 5 | May 2022

Hidrotechnics Prevent Vibrations that Occur in Constructions

Muminov Oybek Alisher ugli

Doctorate, Fergana polytechnic institute, Republic of Uzbekistan o.muminov@ferpi.uz

Sulaymonova Durdona Boburjonovna

Magistrate, Fergana polytechnic institute, Republic of Uzbekistan durdonasulajmonova01@gmail.com

Annotation: The preservation of the hydrotechnical structures from the vibration phenomenon is due to the Reserve work, which is carried out taking into account the circumstances associated with an increase or decrease in the flow in the project, an increase in the flood arrival time, a complete cessation of the water discharge pipeline, these works are completely received from the vibration phenomenon and the

Keywords: cavitation, erosion, vibration, thermal efficiency, multi-phase liquid, dynamics.

Introduction: Finding the normal suction height of HES turbines, the emergence of cavitation processes at heights above or below this suction height, causes a meeting of vibrations of the HES and its construction. As a result of the deepening of the working wheel, the vibration of the entire system is observed, which leads to the penetration of cavitation into erosion. Such changes davriy will require that there will be repair work in progress. But as it turned out, in order to eliminate the vibration effect due to the absorption of cavitation erosion, it is useful to make a small deepening of the working building, provided that the working wheel is repaired.

Main body: In order to protect erosion objects, such as landscaping or cavitation, producing manual farming. As more and more people leave their homes, they increasingly turn to us.

 $K > K_{\kappa p}$

Here: K is the cavitation parameter, K_{KR} is the cavitation parameter, which is critical. For some types of energy sinks and flow separators, K_{KR} values are given in.

From this it can be seen that the less the tension to the extinguishers leads to a decrease in its K_{KR} coefficient, which means that it improves the cavitation properties of the extinguisher, thereby allowing it not to suffer cavitation even at very high speeds, but this situation leads to a decrease in the energy absorption properties of the extinguisher.

Gawlika and the science of water problems are still needed, has not reached the level of detection of various types of temporary injuries through the accounting of the growth process. But with the help of calculations it is possible to make reliable decisions on the protection of structures from vibrations.

In all of the above water bodies and pipes, various dissolved substances in running water, solid granules, whitewash in nature pure water itself is much less than threeraydi. Small vibrations in the water also lead to large fluctuations, so the fluid under consideration forms a complex multi-phase liquid.

In the works of the above scientists and in the works of other authors, the methods that determine the rotational motion in water discharges required accuracy, otherwise the expected result in the design, exploitation of the gidroinshoot will not be obtained. The nature and legality of the currents coming out of the pipes and from the

© 2022, IJOT | Research Parks Publishing (IDEAS Lab) www.researchparks.org | Page 71



 $https://journals.researchparks.org/index.php/IJOT \\ e-ISSN: 2615-8140 \mid p-ISSN: 2615-7071$

Volume: 4 Issue: 5 | May 2022

water dumps, along the pipe, into circulation, has not been fully studied. There is no stagnation of flow in connection with the occurrence of cross-circulation in the pipes conducting a water-carrying vortex.

The flow is transformed and flows with a spiral shape over the entire length of the pipe. The rotation axis of the spiral current is have, first the rotation axis is tilted and the swirling pinwheel looks. Then, under the influence of an irregular current, the swirling coil breaks down and rotates together with the current. After rotation, a few large swirls form in the stream, and this condition is called a division of swirls. The process of whirling and the division of the current into several streams occurs through the dynamics of the emergence of large energy.

This process occurs through speed pulsations, and in the flow mode, enhanced turbulence occurs. The stagnation in the stream disappears and a cross-circulatory flow occurs, the flow type changes to the circulating stream.

Any type of current is divided into two characteristic spheres:

The Central sphere with a whirlpool (Whirlpool core), that is, the sphere with a large whirlpool, that is, the sphere with a small Whirlpool, which is outside the sphere.

The swirling field is a non-standard field of flow, in this area there are excitation, the deviation of the flow from the symmetry axis is observed, and as a result of this, the circulation is burned, and the centrifugal force field that stabilizes the flow is burned. The flow passes from the symmetrical form to the spiral form, without being able to suppress non-symmetrical excitation.[1,2]

As a result of the subsequent reduction in circulation, the circulatory flow ends completely and becomes a weak circulating current.

High-speed pipe and as a result of a decrease in the hydrodynamic pressure of flowing streams in the canl causes the release of oxygen from the water. This process creates a two-phase flow consisting of water and air.

Due to a decrease in pressure in the air mixture in the water in the tapered pipe, a cavitation process occurs, which leads to a violation of the hydro technical structure by removing the pulsation and vibration gel.

As an example, we can see that the construction of the 185m dam on the project was planned at the Hidrotechnical complex. From the process of exploitation, when the pressure reaches 105m, dangerous situations begin to arise in the water discharge plant. When the flow rate reached 25 m/s, the stagnant movement of the flow began, and in the water discharge system, a 5.5-point vibration process began.[3,4]

As is known, cavitation is a murracean process, cavitation produces pulses and vibrations. And these processes completely change the flow regime, that is, the flow passes from a calm state to a complex developed turbulent state. In the stream there are swirls, circulatory States relative to the arrow. In such cases, as a result of interaction, a rise in temperature in the flow is observed. To characterize the cavitation prosses, we use the coefficient of cavitation.

$$K = \frac{H_{\text{xap}} - H_{\text{kp}}}{v_{\text{xap}}^2 / 2_g}$$

At constant temperature, through static and dynamic pressures, constant pressure in the flow occurs, or there is a decrease in pressure. Due to the decrease in pressure, the vapor bubbles in the stream begin to form, increasing along the flow and turning into caverns. Due to the fact that the pressure in the caverns is greater than the pressure in the liquid, it exits to the surface of the flow crack, there is a phenomenon of pulsation and cavitation in the flow, vibration in the pipes begins.[5,6]

Conclusion: In addition to the fact that the cavitation process produces vibration gel, the migration along the cavitation stream causes the formation of non-condensing gas bubbles, caverns in the stream. Gas bubbles in the

Attribution License (CC BY). To view a copy of this license, visit https://creativecommons.org/licenses/by/4.0/

© 2022, IJOT | Research Parks Publishing (IDEAS Lab) www.researchparks.org

Page 72



https://journals.researchparks.org/index.php/IJOT e-ISSN: 2615-8140 | p-ISSN: 2615-7071 Volume: 4 Issue: 5 | May 2022

stream, Cavernas go up, narrow and then burst. Such non-stationary gas bubbles also appear in the walls of the caverns, due to low pressure near the wall.

REFERENCE

- 1. Ishankulovich, K. S. (2022). Modeling The Rotation Of A Turbulent Flow With A Variable Radius. *International Journal of Progressive Sciences and Technologies*, 31(2), 388-395.
- 2. Mo'minov, O. A., & O'tbosarov Sh, R. TYPE OF HEATING RADIATORS, PRINCIPLES OF OPERATION AND THEORETICAL ANALYSIS OF THEIR TECHNICAL AND ECONOMIC CHARACTERISTICS.
- 3. Abdukarimov, B. A., & Kuchkarov, A. A. (2022). Research of the Hydraulic Resistance Coefficient of Sunny Air Heaters with Bent Pipes During Turbulent Air Flow. Journal of Siberian Federal University. Engineering & Technologies, 15(1), 14-23.
- 4. Abdukarimov, B. A. (2021). Improve Performance Efficiency As A Result Of Heat Loss Reduction In Solar Air Heater. International Journal of Progressive Sciences and Technologies, 29(1), 505-511.
- 5. Malikov, Z. M., & Madaliev, M. E. (2020). Numerical simulation of two-phase flow in a centrifugal separator. Fluid Dynamics, 55(8), 1012-1028.
- 6. Маликов, 3. М., & Мадалиев, М. Э. (2021). Численное моделирование течения в плоском внезапно расширяющемся канале на основе новой двужидкостной модели турбулентности. Вестник Московского государственного технического университета им. НЭ Баумана. Серия «Естественные науки», (4 (97)), 24-39.
- 7. Madraximov, M. M., Abdulkhaev, Z. E., & ugli Inomjonov, I. I. (2022). Factors Influencing Changes In The Groundwater Level In Fergana. International Journal of Progressive Sciences and Technologies, 30(2), 523-526.
- 8. Arifjanov, A., Otaxonov, M., & Abdulkhaev, Z. (2021). Model of groundwater level control using horizontal drainage. Irrigation and Melioration, 2021(4), 21-26.
- 9. Худайкулов, С. И., & Муминов, О. А. У. (2022). МОДЕЛИРОВАНИЯ МАКСИМАЛЬНОЙ СКОРОСТИ ПОТОКА ВЫЗЫВАЮЩЕЙ КАВИТАЦИЮ И РЕЗКОЙ ПЕРЕСТРОЙКИ ПОТОКА. Universum: технические науки, (2-2 (95)), 59-64.
- 10. АБДУЛХАЕВ, 3., & МАДРАХИМОВ, М. (2020). Гидротурбиналар ва Насосларда Кавитация Ходисаси, Окибатлари ва Уларни Бартараф Этиш Усуллари. Ўзбекгидроэнергетика" илмий-техник журнали, 4(8), 19-20.
- 11. ugli Moʻminov, O. A., Maqsudov, R. I., & qizi Abdukhalilova, S. B. (2021). Analysis of Convective Finns to Increase the Efficiency of Radiators used in Heating Systems. Middle European Scientific Bulletin, 18, 84-89.
- 12. Усмонова, Н. А., Негматуллоев, З. Т., Нишонов, Ф. Х., & Усмонов, А. А. (2019). Модели закрученных потоков в строительстве Каркидонского водохранилища. Достижения науки и образования, (12 (53)), 5-9.
- 13. Абдукаримов, Б. А., Аббасов, Ё. С., & Усмонова, Н. У. (2019). Исследование рабочих параметров солнечных воздухонагревателей способы повышения их эффективности. Матрица научного познания, (2), 37-42.
- 14. Мадрахимов, М. М., & Абдулхаев, З. Э. (2019). Насос агрегатини ишга туширишда босимли сув узатгичлардаги ўтиш жараѐнларини хисоблаш усуллари. Фарғона Политехника Институти Илмий—

© 2022, IJOT | Research Parks Publishing (IDEAS Lab) www.researchparks.org | Page 73

https://journals.researchparks.org/index.php/IJOT e-ISSN: 2615-8140 | p-ISSN: 2615-7071 Volume: 4 Issue: 5 | May 2022

Техника Журнали, 23(3), 56-60.

- 15. Mamadalievich, M. M., & Erkinjonovich, A. Z. Principles of Operation and Account of Hydraulic Taran. JournalNX, 1-4.
- 16. Сатторов, А. Х. (2016). СУЩЕСТВОВАНИЕ И ПРЕДСТАВЛЕНИЕ ОГРАНИЧЕННОГО РЕШЕНИЯ ОДНОГО КВАЗИЛИНЕЙНОГОДИФФЕРЕНЦИАЛЬНОГО УРАВНЕНИЯ. Іп Вузовская наукарегиону (рр. 126-132).
- 17. Мадхадимов, М. М., Абдулхаев, З. Э., & Сатторов, А. Х. (2018). Регулирования работы центробежных насосов с изменением частота вращения. Актуальные научные исследования в современном мире, (12-1), 83-88.
- 18. Abdikarimov, R., Usarov, D., Khamidov, S., Koraboshev, O., Nasirov, I., & Nosirov, A. (2020, July). Free oscillations of three-layered plates. In IOP Conference Series: Materials Science and Engineering (Vol. 883, No. 1, p. 012058). IOP Publishing.
- 19. Nosirov, A. A., & Nasirov, I. A. (2021). Natural and Forced Vibrations of Axisymmetric Structure Taking into Account the Viscoelastic Properties of the Base. Middle European Scientific Bulletin, 18, 303-311.
- 20. qizi Abdukhalilova, S. B. (2021). Simplified Calculation of the Number of Bimetallic Radiator Sections. CENTRAL ASIAN JOURNAL OF THEORETICAL & APPLIED SCIENCES, 2(12), 232-237.
- 21. Maqsudov, R. I., & qizi Abdukhalilova, S. B. (2021). Improving Support for the Process of the Thermal Convection Process by Installing. Middle European Scientific Bulletin, 18, 56-59.
- 22. Мадрахимов, М. М., Абдулхаев, З. Э., & Ташпулатов, Н. Э. (2019). Фарғона Шахар Ер Ости Сизот Сувлари Сатхини Пасайтириш. Фарғона Политехника Институти Илмий-Техника Журнали, 23(1), 54-58.
- 23. Hamdamov, M., Mirzoyev, A., Buriev, E., & Tashpulatov, N. (2021). Simulation of non-isothermal free turbulent gas jets in the process of energy exchange. In E3S Web of Conferences (Vol. 264, p. 01017). EDP Sciences.
- 24. Рашидов, Ю. К., Орзиматов, Ж. Т., & Исмоилов, М. М. (2019). Воздушные солнечные коллекторы: перспективы применения в условиях Узбекистана. Іп Экологическая, промышленная и энергетическая безопасность-2019 (рр. 1388-1390)
- 25. Рашидов, Ю. К., Исмоилов, М. М., Орзиматов, Ж. Т., Рашидов, К. Ю., & Каршиев, Ш. Ш. (2019). Повышение эффективности плоских солнечных коллекторов в системах теплоснабжения путем оптимизации их режимных параметров. Іп Экологическая, промышленная и энергетическая безопасность-2019 (рр. 1366-1371).
- 26. Madraximov, M. M., Abdulkhaev, Z. E., & Orzimatov, J. T. (2021). GIDRAVLIK TARAN OURILMASINING GIDRAVLIK HISOBI. Scientific progress, 2(7), 377-383.
- 27. Rashidov, Y. K., & Orzimatov, J. T. (2022). SOLAR AIR HEATER WITH BREATHABLE MATRIX ABSORBER MADE OF METAL WIRE TANGLE. Scientific-technical journal, 5(1), 7-13.
- 28. Усаров, М. К., & Маматисаев, Г. И. (2019). КОЛЕБАНИЯ КОРОБЧАТОЙ КОНСТРУКЦИИ КРУПНОПАНЕЛЬНЫХ ЗДАНИЙ ПРИ ДИНАМИЧЕСКИХ ВОЗДЕЙСТВИЯХ. Іп Научный форум: технические и физико-математические науки (рр. 53-62).
- 29. Abdukarimov, B., O'tbosarov, S., & Abdurazakov, A. (2021). Investigation of the use of new solar air heaters



https://journals.researchparks.org/index.php/IJOT e-ISSN: 2615-8140 | p-ISSN: 2615-7071 Volume: 4 Issue: 5 | May 2022

for drying agricultural products. In E3S Web of Conferences (Vol. 264, p. 01031). EDP Sciences.

- 30. Усаров, М. К., & Маматисаев, Г. И. (2014). К динамическому расчету коробчатой конструкции здания. МЕ' MORCHILIK va QURILISH MUAMMOLARI, 86.
- 31. Bekzod, A. (2020). Relevance of use of solar energy and optimization of operating parameters of new solar heaters for effective use of solar energy. IJAR, 6(6), 16-20.
- 32. Madraximov, M. M., Nurmuxammad, X., & Abdulkhaev, Z. E. (2021, November). Hydraulic Calculation Of Jet Pump Performance Improvement. In International Conference On Multidisciplinary Research And Innovative Technologies (Vol. 2, pp. 20-24).
- 33. Hamdamalievich, S. A., & Nurmuhammad, H. (2021). Analysis of Heat Transfer of Solar Water Collectors. Middle European Scientific Bulletin, 18, 60-65.
- 34. Madaliev, M. E. U., Maksudov, R. I., Mullaev, I. I., Abdullaev, B. K., & Haidarov, A. R. (2021). Investigation of the Influence of the Computational Grid for Turbulent Flow. Middle European Scientific Bulletin, 18, 111-118.
- 35. Madraximov, M., Yunusaliev, E., Abdulhayev, Z., & Akramov, A. (2021). Suyuqlik va gaz mexanikasi fanidan masalalar to'plami. GlobeEdit.
- 36. Абдукаримов, Б. А., Акрамов, А. А. У., & Абдухалилова, Ш. Б. К. (2019). Исследование повышения коэффициента полезного действия солнечных воздухонагревателей. Достижения науки и образования, (2(43)).
- 37. Умурзакова, М. А., Усмонов, М. А., & Рахимов, М. Н. (2021). АНАЛОГИЯ РЕЙНОЛЬДСА ПРИ ТЕЧЕНИЯХ В ДИФФУЗОРНО-КОНФУЗОРНЫХ КАНАЛАХ. Экономика и социум, (3-2), 479-486.
- 38. Аббасов, Ё. С., & Умурзакова, М. А. (2020). РАСЧЕТ ЭФФЕКТИВНОСТИ ПЛОСКИХ СОЛНЕЧНЫХ ВОЗДУХОНАГРЕВАТЕЛЕЙ. In Современные проблемы теплофизики и энергетики (рр. 7-8).